



72'-11" +/-

GENERAL NOTES:

1. REATTACH ELECTRICAL CONDUITS, WIRING, SMOKE DETECTORS, AND LIGHTING FIXTURES (TEMPORARILY RELOCATED DURING DEMOLITION) TO NEW FRAMING.

KEYED NOTES:

1. AT WORK AREA A - NEW ROOFING SYSTEM ON NEW METAL DECK. COMPRESSED GRANULES, 1/2" GYPSUM BOARD, 2" POLYURETHANE INSULATION, 1/2" GYPSUM BOARD, AND 3/4" UP ROOFING. DRAINAGE SHALL BE ACCOMPLISHED BY INSTALLATION OF A WARPED METAL DECK (SEE STRUCTURAL). INSULATION THICKNESS SHALL A CONSTANT 8" THICK EXCEPT AT PERIMETER WHERE CRICKETS SHALL BE PROVIDED.
2. AT WORK AREA B - NEW ROOFING SYSTEM ON NEW METAL DECK. COMPRESSED GRANULES, 1/2" GYPSUM BOARD, 2" POLYURETHANE INSULATION, 1/2" GYPSUM BOARD, AND 3/4" UP ROOFING. DRAINAGE SHALL BE ACCOMPLISHED BY INSTALLATION OF A SLOPING METAL DECK (SEE STRUCTURAL). INSULATION THICKNESS SHALL A CONSTANT 8" THICK EXCEPT AT PERIMETER WHERE CRICKETS SHALL BE PROVIDED.
3. NEW FLASHING.
4. PROVIDE PRE-FABRICATED CRICKET AT PLASTER TOPS. (SEE 7/A6)
5. NEW ROOF DRAIN - CONNECT TO NEW PILING. (SEE 1/A6)
6. PROVIDE NEW SCUPPER IN PLACE OF DEMOLISHED SCUPPER. (SEE 2/A6)
7. NEW OVERFLOW SCUPPER. (SEE 2/A6)
8. NEW FLASHING AT VENTS THROUGH THE ROOF. (SEE 4/A6)
9. NEW FLASHING FOR MECHANICAL EQUIPMENT ON ROOF. (SEE 5/A6)
10. NEW ROOF HATCH. (SEE 3/A6)
11. NEW WALK PAND - 4'-0" SQUARE UNLESS OTHERWISE DIMENSIONED.
12. NEW PARAPET.
13. PROVIDE NEW METAL SILING ON NEW FRAMED WALL AND PARAPET.
14. NEW STEEL ROOF LADDER. (SEE 6/A6)

1 ARCHITECTURAL ROOF PLAN

