



LEGEND:
 [Symbol] EXISTING CONCRETE ATTIC FLOOR (2ND FLOOR CEILING)

- KEYED NOTES:**
- 1 EXISTING STEEL BEAM TO REMAIN.
 - 2 EXISTING CEILING JOISTS TO REMAIN.
 - 3 EXISTING CONCRETE BEAM OR CLIP TO REMAIN.
 - 4 EXISTING OPENING FOR ATTIC ACCESS FROM 2ND FLOOR TO REMAIN.
 - 5 NEW ROOF HATCH ABOVE TO REPLACE EXISTING.
 - 6 EXISTING LADDER TO ROOF HATCH TO REMAIN.
 - 7 SUPPORT NEW ROOF STRUCTURE ON EXISTING CEILING BEAMS, CONCRETE CHAIRS, AND EXTERIOR WALLS. (SEE STRUCTURAL.)
 - 8 PROVIDE 4" MINIMUM URETHANE FOAM INSULATION ON EXTERIOR WALL BETWEEN EXISTING CEILING AND UNDERSIDE OF NEW STEEL DECK. PROVIDE SPARKED-ON PREPARED AND WIND RESISTANT.
 - 9 FILL IN EXISTING OPENING WITH CONCRETE TO THICKNESS OF EXISTING WALL ALLOWING A 4" DEPRESSION FROM THE EXTERIOR WALL PLANE. PAINT EXTERIOR TO MATCH EXISTING COLOR SCHEME. COORDINATE WITH TASKS ACCOMPLISHED UNDER WORK AREA 9 DESCRIBED ON SHEET 02.
 - 10 PROVIDE NEW CEILING IN EXISTING STRUCTURE WITH 5/8" GYPSUM BOARD, PAINTED, ON 2x8 WOOD JOISTS IN 18" O.C.

1 ARCHITECTURAL ATTIC PLAN
 1/8" = 1'-0"

